



## BA 30X3.5 V4A R25M (860 325)



Figure without obligation

Stainless steel strip according to EN 62561-2, for lightning protection systems and ring equipotential bonding.

Stainless steel strip for use in soil have to be made of StSt (V4A) with a molybdenum content > 2 % e.g. 1.4571, 1.4404 in accordance with EN 62561-2, IEC/EN 62305-3 and DIN VDE 0151.

Type	BA 30X3.5 V4A R25M
Part No.	860 325 ✓
Width	30 mm
Thickness	3.5 mm
Cross-section	105 mm <sup>2</sup>
Material	StSt (V4A)
Material No.	1.4571 / 1.4404
ASTM / AISI:	316Ti / 316L
Standard	EN 62561-2
Conductivity	≥ 1.25 m / Ohm mm <sup>2</sup>
Resistivity	≤ 0.8 Ohm mm <sup>2</sup> / m
Short-circuit current (AC 50 Hz / DC) (1 s; ≤ 300 °C)	3.9 kA
Length tolerance	+/- 5%
Weight	825 g/m
Customs tariff number (Comb. Nomenclature EU)	72202021
GTIN	4013364093157
PU	25 m

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

Strips in different dimensions and materials are available upon request.